


COMPRESSORI-ASPIRATORI A CANALE LATERALE

**SIDE CHANNEL
COMPRESSORS AND
VACUUM PUMPS**

SC502SF

SC502SF3.0T-IE2 – SC502SF4.0T-IE2



Costruiti secondo il principio dei canali laterali, funzionano sia in aspirazione sia in compressione e sono progettati per lavorare a servizio continuo. Realizzato in alluminio pressofuso garantisce la massima robustezza e maneggevolezza. Non occorre lubrificazione in quanto non c'è contatto tra le parti statiche e rotanti. Particolari silenziosi contribuiscono ad ottenere un elevato livello di silenziosità.

Construction of the ring blowers fans is based on the lateral ducts principle. The blowers can operate as either exhaust or compression fans and are designed for continuous service. The device is assembled directly on the motor shaft; all the rotating parts are dynamically balanced to ensure absolute absence of vibration. Full die-cast aluminium construction for maximum sturdiness and ease of handling.



Curve Curva n.	Model Modello n.	Frequency Frequenza (Hz)	Output power Potenza (kW)	Voltage Vtaggio (V)	Rated current Assorbimento (A)	Noise Rumorosità dB (A)	Weight Peso (Kg)
1	SC502SF3.0T-IE2	50	3.0	230/400	10.7 Δ/6.2Y	72	39
2	SC502SF3.0T-IE2	60	3.45	260/460	10.1 Δ/5.8Y	74	39
3	SC502SF4.0T-IE2	50	4	400/690	8.0 Δ/4.6Y	72	43
4	SC502SF4.0T-IE2	60	4.6	460/720	7.5 Δ/4.3Y	74	43



I.VA.CO s.r.l.


Via delle Brigole, 33
23877 Paderno D'Adda (LC)

Tel. +39 03909281084


www.ivaco.it

sales@ivaco.it

ASPIRAZIONE / EXHAUST



COMPRESSIONE / COMPRESSION



I valori di portata e pressione si intendono per il convogliamento dell'aria avente in aspirazione temperature di 15°, densità di 1,23 kg/m³ e pressione a 1.013 mbar. La tolleranza di queste curve si intende del ±10%. I dati sopraindicati possono essere variati senza preavviso.


The characteristic data given here refer to the handling of gas with inlet temperature of 15° C, normal density of 1,23 kg/m³ and absolute pressure of 1.013 mbar. Tolerance of ±10%. The data may change without any notification.

a i r m o v i n g




COMPRESSORI-ASPIRATORI A CANALE LATERALE

**SIDE CHANNEL
COMPRESSORS AND
VACUUM PUMPS**

SC502SF3.0T-IE2 – SC502SF4.0T-IE2



Dimensioni / Dimensions = mm



I.VA.CO s.r.l.

Via delle Brigole, 33
23877 Paderno D'Adda (LC)

Tel. +39 03909281084

www.ivaco.it

sales@ivaco.it

	Phase Fase	A	A'	B	C	D	E	F	G	H	H'	J	K	L	M	N	O	P	Q	ØR	S	T	U	V	V'	V1	V1'	a	ØX	YxZ	X-holes X-fori
SC502SF3.0T-IE2	3	372	411	371	60	260	295	465	190	175	144	135	115	155	98	171	48	G2"	83	14	4	116	M8x17	4 x M 32 x1.5	23.5°	200	M8 x 20	51°/171°/291°			
SC502SF4.0T-IE2	3	372	411	371	60	260	295	499	224	175	144	135	115	155	98	171	48	G2"	83	14	4	116	M8x17	4 x M 32 x1.5	23.5°	200	M8 x 20	51°/171°/291°			

a i r m o v i n g